



***METOLIUS***

***Equalizer***

Metolius Equalizer is a compact, light, and convenient way to equalize multiple anchor points at belays.

- Lengths: 10' (3 M), 15' (4.5 M)
- Weights: 10' - 5.1 oz (143 g), 15' - 6.9 oz (196 g)
- Strength: 22 kN (4950 lbf) when used as a looped sling or two/three point anchor. 15 kN (3400 lbf) kN when used end-to-end



To equalize a 3-point anchor, clip each sewn loop into one of the outer anchor points.



Clip the middle of the sling into the 3rd point to form 2 loops.



Equalize the 2 loops of webbing in the intended direction of load and tie an overhand knot on a bight.



To equalize a 2-point anchor, clip both sewn loops into one point and the middle of the sling into the other point. Equalize in the intended direction of load and tie an overhand knot on a bight.



To use as a full-length sling, connect the end loops with a locking carabiner.



Reinforced end-loops provide additional full-strength clip in points. Note that the secondary load in the end-loop is not equalized between the multiple anchor points. It is merely backed up to the other anchor points. Only use the end-loop as an additional clip in point if the single anchor point it is on is sufficient to carry the load alone.



Use the handy, integrated pocket for easy, compact storage.

**Warning: The Equalizer is intended to be used in one of the configurations described herein (i.e. always have multiple strands of webbing equalized to bear the load), and never as a single strand of webbing. If used as a single strand, the breaking strength is 15 kN (3400 lbf).**